

SPECIFICATIONS

- RGB + White color system
- Standard lens 12°
- Electronic dimmer
- Electronic strobe, synchronized, random, pulse
- Pan 538°, Tilt 230°, 16 bit
- Flicker-free

PHYSICAL SIZE

- Length: 335 mm (13.20 in)
- Width: 350 mm (13.8 in)
- . Height: 470 mm (18.5 in), head straight up
- Weight: 11.2 kg (25 lbs)

LIGHT SOURCE

• 37 Luxeon leds, 1.2 W each, 12 Red, 12 Green, 12 Blue, 1 White

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- DMX channels: 12
- · Setting and addressing: led display or remotely

ELECTRICAL SPECIFICATIONS/ CONNECTIONS

- AC power: 100/115/208/230/240 V, 50/60 Hz, 2m (6.6 ft) integral cable without power plug
- Power consumption: 0.6 A at 230V, 1.2 A at 115V
- DMX data in/out: 3 pin locking XLR

ACCESSORIES

• 30° lens kit (#KIT102)

KEY FEATURES

- Bright as a 250 W fixture, with 75% energy saving
- Cosmetic designed for hi-end installations
- White led for color variation tone
- Digital strobe
- Variable light projection angle
- Low maintenance

