

PinLite Led

SPECIFICATIONS

- RGB color mixing
- Standard lens 12°
- Electronic dimmer
- Electronic strobe, synchronized, random, pulse effect
- Double yoke for easy ground standing or truss hanging

PHYSICAL SIZE

- Length: 127 mm (5.0 in)
- Width: 152.4 mm (6.0 in)
- Height: 127 mm (5.0 in)
- Weight: 1.8 kg (4.0 lbs)

LIGHT SOURCE

- 12 Luxeon leds, 1.2 W each, 4 Red, 4 Green, 4 Blue

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- Dmx channels: 6

- Setting and addressing: binary dip switch or remotely
- 4 Internal automatic programs

ELECTRICAL SPECIFICATIONS/CONNECTIONS

- AC power: 90-250 V, auto sensing, 50/60 Hz, 2m (6.6 ft) integral cable without power plug
- Power consumption: 0.18 A at 230 V, 0.45 A at 115 V
- DMX data in/out: 3 pin locking XLR

OPTIONS

- 30° lens kit (# 9186)
- 40°x13° elliptical lens kit (# 9186/2)
- 110° flood reflector (# 9187)
- Frame for internal frost filter (# 9188)
- Frame for external frost filter (# 9188/1)
- 4 leaf barndoor (# 9164)
- IP 65 rear panel (black: # 10, silver: # 10/1)
- 5 pin locking XLR (# 9189)



PinLite Led - # 9180
argento / silver
PinLite Led - # 9180/1
nero / black

